


# EARTHMAX SR 49 M



<b>TIRE SIZE</b>	<b>29.5 R 25</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	BULLDOZER / CHARGEUR- TRANSPORTEUR LHD / CHARGEUR / TOMBREAU SURBAISSÉ
<b>VERSION</b>	CUT RESISTANT COMPOUND
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	200 B ; 216 A2

## DIMENSIONS IS STANDARD

<b>OD (MM)</b>	1905	<b>TRA CODE</b>	E4/L4
<b>SLR (MM)</b>	844	<b>STAR RATING</b>	★★
<b>RC (MM)</b>	5600		
<b>RIM REC</b>	25.00/3.5		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	4.00	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25	6.50
50	11500	11800	12500	12850	13600	14000	-	-	-	-	-
10	-	-	-	-	-	19000	19500	20000	20600	21200	22400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.