

FLOTATION 648

TIRE SIZE	600/55 - 22.5
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	HEUPRESSE / ERNTEMASCHINE / STREUMASCHINE / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
VERSION	DUAL BEAD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	160 A8/156 B
LI/SS FREE ROLLING	173 A8/169 B



ABMESSUNGEN US STANDARD

USA-CODE	94045280	RC (IN)	146.3
SW (IN)	23.6	RIM REC	AG 20.00
OD (IN)	48.4	ECE	E11-106R-004393
SLR (IN)	21.3	PR	20

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	44	45	46
5 FR	19320	19690	20060
10 FR	17390	17720	18050
20 FR	15450	15750	16050
25 FR	13800	14060	14330
30 FR	12420	12650	12790
5 DW	13380	13620	13890
10 DW	12040	12270	12500
20 DW	10700	10900	11110
25 DW	9560	9730	9920
30 DW	8600	8760	8820

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.