

# AGRIMAX RT 855

|                  |                                                                       |
|------------------|-----------------------------------------------------------------------|
| <b>TIRE SIZE</b> | <b>280/85 R 24</b>                                                    |
| <b>UM</b>        | US STANDARD                                                           |
| <b>MACHINERY</b> | SPRAYER / VINEYARD HARVESTER /<br>TRACTOR / HARVESTER /<br>IMPLEMENTS |
| <b>VERSION</b>   | SPECIAL                                                               |
| <b>TL/TT</b>     | TL                                                                    |
| <b>LI/SS</b>     | 115 A8/B                                                              |



## DIMENSIONS US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA CODE</b> | 94044658 | <b>RC (IN)</b> | 126.9          |
| <b>SW (IN)</b>  | 11.5     | <b>RIM REC</b> | W 10           |
| <b>OD (IN)</b>  | 42.8     | <b>RIM ALT</b> | W 9            |
| <b>SLR (IN)</b> | 19.4     | <b>ECE</b>     | E4-106R-000611 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI   | 9    | 12   | 15   | 17   | 20   | 23   |
|-------------|------|------|------|------|------|------|
| <b>30</b>   | 1480 | 1720 | 1960 | 2200 | 2450 | 2680 |
| <b>25</b>   | 1480 | 1720 | 1960 | 2200 | 2450 | 2680 |
| <b>20</b>   | 1590 | 1850 | 2110 | 2370 | 2620 | 2880 |
| <b>5 LT</b> | 1980 | 2300 | 2620 | 2950 | 3270 | 3590 |
| <b>5 HT</b> | 1590 | 1850 | 2110 | 2370 | 2620 | 2880 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.