

AGRIMAX RT 765

TIRE SIZE	200/70 R 16
UM	US STANDARD
MACHINERY	FELDSPRITZE / TRACTOR / TRAUBENERNTEMASCHINE / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	94 A8/B



ABMESSUNGEN US STANDARD

USA-CODE	94026869	RIM REC	W 6
SW (IN)	7.8	RIM ALT	W 7
OD (IN)	27.0	ECE	E4-106R-000607
SLR (IN)	12.4	TRA CODE	R1W
RC (IN)	81.1	TREAD DEPTH (32nd)	32.13

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
30	690	800	930	1040	1160	1280	1380	1480
25	690	800	930	1040	1160	1280	1380	1480
20	750	860	990	1110	1250	1370	1480	1590
5 LT	940	1080	1230	1390	1550	1710	1850	1980
5 HT	750	860	990	1110	1250	1370	1480	1590

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.