


AGRIMAX RT 855

| | |
|---------------------|--|
| TIRE SIZE | 320/85 R 38 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | FELDSPRITZE / TRAUBENERNTEMASCHINE / TRACTOR / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE |
| VERSION | SPECIAL |
| TIRE TYPE | TL |
| LI/SS | 143 A8/B |



ABMESSUNGEN IS STANDARD

| | | | |
|-----------------|------|----------------|--------------------|
| SW (MM) | 329 | RIM REC | W 11 |
| OD (MM) | 1509 | RIM ALT | W 9 ; W 10 ; DW 10 |
| SLR (MM) | 700 | ECE | E4-106R-000781 |
| RC (MM) | 4580 | SRI | 725 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 |
|------------|------|------|------|------|------|------|------|------|------|
| 50 | 985 | 1145 | 1500 | 1830 | 1990 | 2130 | 2320 | 2510 | 2725 |
| 40 | 985 | 1145 | 1500 | 1830 | 1990 | 2130 | 2320 | 2510 | 2725 |
| 30 | 1055 | 1230 | 1610 | 1960 | 2135 | 2280 | 2485 | 2690 | 2920 |
| 10 LT | 1320 | 1540 | 2015 | 2450 | 2670 | 2855 | 3110 | 3365 | 3655 |
| 10 HT | 1055 | 1230 | 1610 | 1960 | 2135 | 2280 | 2485 | 2690 | 2920 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.