

# AW 705

<b>TIRE SIZE</b>	<b>15.0/70 - 18</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	ПРЕСС-ПОДБОРЩИК / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	148 A8



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	405	<b>RIM REC</b>	13.00
<b>OD (MM)</b>	1010	<b>RIM ALT</b>	13; W 13
<b>SLR (MM)</b>	447	<b>ECE</b>	E4-106R-001903
<b>RC (MM)</b>	3092	<b>PR</b>	14

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.60
10 FR	4410
25 FR	3750
30 FR	3530
40 FR	3150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.