

# MP 567

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | 16.0/70 - 20  |
| <b>UM</b>           | US STANDARD   |
| <b>CONSTRUCTION</b> | ⊠ BIAS  |
| <b>MACHINERY</b>    | ATTREZZI AGRICOLI / SOLLEVATORE<br>TELESCOPICO / ATTREZZI AGRICOLI /<br>SOLLEVATORE TELESCOPICO /<br>VEICOLO UNIVERSALE |
| <b>VERSIONE</b>     | STANDARD  |
| <b>TIRE TYPE</b>    | TT  |



## DIMENSIONI US STANDARD

|                   |          |                |                |
|-------------------|----------|----------------|----------------|
| <b>CODICE USA</b> | 94015108 | <b>RC (IN)</b> | 131.9          |
| <b>SW (IN)</b>    | 15.9     | <b>RIM REC</b> | 13 SDC         |
| <b>OD (IN)</b>    | 44.4     | <b>RIM ALT</b> | 12             |
| <b>SLR (IN)</b>   | 19.3     | <b>ECE</b>     | E4-54R-0022639 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 51   |
|-----------|------|
| 55        | 6390 |
| 25        | 7360 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.