


# AGRIMAX RT 955

	<b>340/85 R 48</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ILAÇLAMA / ÜZÜM HASAT MAKINESİ / BIÇERDÖVER / UYGULAMALI MAKİNE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
	152 A8/B



## UNDEFINED US STANDARD

<b>USA CODE</b>	94029426	<b>RC (IN)</b>	219.4
<b>SW (IN)</b>	13.9	<b>RIM REC</b>	W 12
<b>OD (IN)</b>	70.7	<b>RIM ALT</b>	W 11
<b>SLR (IN)</b>	33.7	<b>ECE</b>	E4-106R-000800

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	17	23	29	35	41	46	52	58	64
30	3050	4000	4860	5320	5640	6180	6730	7290	7830	-
25	3050	4000	4860	5320	5640	6180	6730	7290	7830	-
20	3270	4280	5200	5700	6040	6620	7210	7790	8380	-
5	3650	4590	5640	6700	7750	7990	8930	9870	10800	11740

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.