

# IT 400

**8.25 - 15**

|                     |                          |
|---------------------|--------------------------|
| <b>UM</b>           | IS STANDARD              |
| <b>CONSTRUCTION</b> | BIAS                     |
| <b>MACHINERY</b>    | DÜŞÜK PLATFORMLU TREYLER |
| <b>VERSION</b>      | STANDARD                 |
| <b>TIRE TYPE</b>    | TT                       |
|                     | 129/125 J                |



## UNDEFINED IS STANDARD

|                 |      |                |                    |
|-----------------|------|----------------|--------------------|
| <b>SW (MM)</b>  | 239  | <b>RIM REC</b> | 6.50               |
| <b>OD (MM)</b>  | 846  | <b>RIM ALT</b> | 6.0 ; 7.0          |
| <b>SLR (MM)</b> | 377  | <b>ECE</b>     | E11E11-54R-0018586 |
| <b>RC (MM)</b>  | 2513 | <b>PR</b>      | 14                 |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 8.60 | 7.90 | 7.20 |
|------------|------|------|------|
| 15         | 2960 | -    | -    |
| 30         | -    | 2440 | -    |
| 100 LS     | -    | 1850 | -    |
| 100 LD     | -    | -    | 1650 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.