


# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>320/85 R 36</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	IRRORAZIONE / VENDEMMIATRICE / TRATTORE / MIETITREBBIA / ATTREZZI AGRICOLI
<b>VERSIONE</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	128 A8/B



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94033065	<b>RC (IN)</b>	173.4
<b>SW (IN)</b>	13.0	<b>RIM REC</b>	W 11
<b>OD (IN)</b>	57.4	<b>RIM ALT</b>	W 9 ; W 10
<b>SLR (IN)</b>	26.5	<b>ECE</b>	E4-106R-000762

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
<b>30</b>	2180	2550	2900	3260	3620	3970
<b>25</b>	2180	2550	2900	3260	3620	3970
<b>20</b>	2350	2730	3110	3490	3880	4250
<b>5 LT</b>	2930	3420	3890	4380	4850	5320
<b>5 HT</b>	2350	2730	3110	3490	3880	4250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.