


AGRIMAX RT 855

TIRE SIZE	250/85 R 22
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	FELDSPRITZE / TRAUBENERNTEMASCHINE / TRACTOR / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	113 A8/B



ABMESSUNGEN US STANDARD

USA-CODE	94062058	RC (IN)	116.7
SW (IN)	9.9	RIM REC	W 8
OD (IN)	38.8	RIM ALT	W 7
SLR (IN)	17.8	ECE	E11-106R-002973

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
30	1200	1380	1580	1770	1980	2180	2360	2540
25	1200	1380	1580	1770	1980	2180	2360	2540
20	1290	1480	1700	1910	2130	2350	2540	2720
5 LT	1610	1840	2120	2390	2670	2930	3170	3410
5 HT	1290	1480	1700	1910	2130	2350	2540	2720

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.