

AS 504

TIRE SIZE	7.50 - 18
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TT
LI/SS DRIVE WHEEL	94 A8
LI/SS FREE ROLLING	106 A8



РАЗМЕРЫ US STANDARD

USA CODE	94026579	RC (IN)	104.3
SW (IN)	8.2	RIM REC	5.50 F
OD (IN)	33.6	RIM ALT	4.50 E; 6.00 F; 5.00 F
SLR (IN)	16.0	PR	6

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	33
5 FR	2930
15 FR	2490
20 FR	2350
25 FR	2090
5 DW	2070
15 DW	1750
20 DW	1650
25 DW	1480

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.