


MULTIMAX MP 527

| | |
|---------------------|--|
| TYRE SIZE | 480/80 R 26 IND |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | COMPACT LOADER / TELEHANDLER / COMPACT LOADER / TELEHANDLER |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS | 160 A8/B |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 479 | RIM REC | DW 15 L |
| OD (MM) | 1428 | RIM ALT | DW 16 L |
| SLR (MM) | 642 | ECE | E11-106R-004069 |
| RC (MM) | 4259 | SRI | 675 |

LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 1.6 | 2.0 | 2.2 | 2.4 | 2.6 | 2.8 | 3.2 | 3.2 | 3.4 | 3.6 |
|------------|------|------|------|------|------|------|------|------|------|-------|
| 50 | 2610 | 3060 | 3330 | 3555 | 3780 | 4005 | 4275 | 4500 | - | - |
| 40 | 2610 | 3060 | 3330 | 3555 | 3780 | 4005 | 4275 | 4500 | - | - |
| 30 | 2795 | 3275 | 3565 | 3805 | 4045 | 4290 | 4575 | 4815 | - | - |
| 25 | 2900 | 3400 | 3700 | 3950 | 4200 | 4450 | 4750 | 4995 | - | - |
| 10 CYC. | 3175 | 3915 | 4255 | 4590 | 4995 | 5335 | 5670 | 6075 | 6415 | 6750 |
| STATIC | 4865 | 6005 | 6525 | 7040 | 7660 | 8180 | 8695 | 9315 | 9835 | 10350 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.