

EARTHMAX SR 31



EARTHMAX
RADIAL OTR TIRES

EARTHMAX SR 31



EARTHMAX SR 31 is an All Steel radial tire specially designed for articulated dump trucks and wheel loaders. It provides extraordinary strength and stability, whilst the non-directional rigid block pattern stands for both excellent traction and maneuverability even on muddy ground. EARTHMAX SR 31 also features a special tread compound which is particularly cut-and-heat resistant. The radial casing structure also provides reduced rolling resistance offering significant fuel savings.



	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TMPH	O.W. (in)	OD (in)	SLR (in)	RC (in)	THREAD DEPTH	VERSION
						REC RIM	ALT RIM							
														
Ø25"	29.5 R 25	TL	L3	**	216 A2	25.00/3.5	-	0	30.1	73.3	32.2	218.7	52.92	CR
	23.5 R 25	TL	E3/L3	**/*	185 B 195 A2	19.50/2.5	-	137	24.1	63.3	28.0	188.9	42.84	CR
	26.5 R 25	TL	E3/L3	**/*	193 B 202 A2	22.00/3.0	-	158	27.1	68.6	30.2	204.7	47.88	CR
	26.5 R 25	TL	L3	**	209 A2	22.00/3.0	-	0	27.1	68.6	30.2	204.7	47.88	CR
	29.5 R 25	TL	E3/L3	**/*	200 B 208 A2	25.00/3.5	-	185	30.1	73.3	32.2	218.7	52.92	CR

CR: CUT RESISTANT COMPOUND

TECHNOLOGIES			PERFORMANCES		
					Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference, SRI index
					

SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TMPH	O.W. (in)	OD (in)	SLR (in)	RC (in)	THREAD DEPTH	VERSION
					REC RIM	ALT RIM							
													
20.5 R 25	TL	E3/L3	**/*	177 B 186 A2	17.00/2.0	--	116					40.32	CR

CR: CUT RESISTANT COMPOUND

TECHNOLOGIES		PERFORMANCES	
 E3/L3	 B	    	 

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index