


# AW 711

|                     |  |
|---------------------|--|
| <b>TYRE SIZE</b>    | <b>15 R 19.5</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | HAY HARVESTER / IMPLEMENT<br>MACHINERY / IMPLEMENTS                                      |
| <b>VERSION</b>      | STUBBLE RESISTANT  |
| <b>TYRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 139 D  |



## DIMENSIONS IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 389  | <b>RIM REC</b> | 11.75           |
| <b>OD (MM)</b>  | 1019 | <b>RIM ALT</b> | 12.75           |
| <b>SLR (MM)</b> | 471  | <b>ECE</b>     | E11-106R-006649 |
| <b>RC (MM)</b>  | 3094 | <b>SRI</b>     | 475             |

## LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 0.8  | 1.2  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.6  | 4.0  | 5.0  | 5.5  |
|------------|------|------|------|------|------|------|------|------|------|------|------|
| 65         | 660  | 855  | 1045 | 1170 | 1365 | 1535 | 1705 | 1850 | 2045 | 2285 | 2430 |
| 50         | 840  | 1090 | 1340 | 1495 | 1745 | 1960 | 2180 | 2365 | 2615 | 2925 | 3110 |
| 40         | 885  | 1145 | 1405 | 1565 | 1830 | 2055 | 2285 | 2480 | 2740 | 3065 | 3260 |
| 25         | 960  | 1245 | 1530 | 1710 | 1995 | 2240 | 2490 | 2705 | 2990 | 3345 | 3555 |
| 10         | 1335 | 1730 | 2125 | 2370 | 2765 | 3110 | 3455 | 3755 | 4150 | 4640 | 4935 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.