


# AGRIMAX V-FLECTO

<b>TIRE SIZE</b>	<b>VF 900/65 R 46</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTEUR DE FORTE PUISSANCE / TRACTEUR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	193 D



## DIMENSIONS US STANDARD

<b>CODE USA</b>	94513703	<b>RC (IN)</b>	271.1
<b>SW (IN)</b>	36.2	<b>RIM REC</b>	DW 30B
<b>OD (IN)</b>	91.1	<b>ECE</b>	E11-106R-0011165
<b>SLR (IN)</b>	39.5		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	11760	13600	15450	17530	19150	20760	23070
<b>FROM 40 TO 25</b>	12930	14960	16990	19270	21040	22820	25350
20	13180	15260	17320	19640	21460	23270	25860
12	13440	15550	17660	20030	21880	23720	26370
5	14220	16450	18680	21190	23140	25100	27890
<b>*UPTO 5 CYC WITH FRONT LOADER</b>	18110	20945	23790	26985	29465	31945	35495
5 HT	13180	15260	17320	19640	21460	23270	25860

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.