


FL 630 SUPER

TIRE SIZE	650/65 R 26.5
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	SPARGITORE / AUTOBOTTE / RIMORCHIO / ATTREZZI AGRICOLI
VERSIONE	STANDARD
TIRE TYPE	TL
LI/SS	174 D



DIMENSIONI IS STANDARD

SW (MM)	645	RIM REC	AG 20.00
OD (MM)	1519	ECE	E4-106R-001651
SLR (MM)	684	SRI	725
RC (MM)	4653		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1955	2260	2565	3115	3600	4150	4700	5065	5615	6100
65	2145	2480	2815	3420	3955	4560	5160	5565	6165	6700
50	2600	3005	3410	4140	4785	5515	6245	6735	7465	8110
40	2920	3375	3830	4650	5380	6200	7020	7570	8390	9115
25	3390	3920	4450	5405	6250	7205	8155	8790	9745	10590
10	3860	4465	5070	6155	7120	8205	9290	10010	11100	12060

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.