


AGRIMAX FORCE

TIRE SIZE	IF 600/70 R 34
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	CEIFEIRA / TRATOR DE ALTA POTENCIA / TRATOR
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS	167 D



DIMENSÕES IS STANDARD

SW (MM)	603	RIM REC	DW 21 B; DW 21 A
OD (MM)	1704	RIM ALT	DW 20 A; DW 20 B
SLR (MM)	757	ECE	E4-106R-001408
RC (MM)	5070	SRI	800

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	2325	2675	3070	3470	3865	4260	4655	4955
FROM 65 TO 40	2560	2940	3375	3815	4250	4685	5120	5450
30	2660	3055	3510	3965	4420	4870	5320	5665
20	2760	3175	3645	4120	4590	5055	5525	5885
10	3250	3730	4285	4845	5395	5945	6500	6920
*UPTO 10 CYC WITH FRONT LOADER	3580	4115	4725	5340	5950	6555	7165	7630
10 HT	2660	3055	3510	3965	4420	4870	5320	5665

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.