


POWERTRAILER SR 331



| | |
|---------------------|--|
| TIRE SIZE | 560/60 R 22.5 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | REMORCĂ / MAȘINI DE IMPLEMENTARE / CISTERNĂ |
| VERSION | IMPLEMENT |
| TIRE TYPE | TL |
| LI/SS | 165 D |

DIMENSIUNI IS STANDARD

| | | | |
|-----------------|----------|----------------|------------------|
| OD (MM) | 1245 | RIM ALT | 17.00; AG18.00 |
| SLR (MM) | 565 | ECE | E11-106R-0010087 |
| RC (MM) | 3775 | SRI | 600 |
| RIM REC | AG 16.00 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 3.2 | 3.6 | 4 | 4.5 | 5 |
|------------|------|------|------|------|------|
| 10 | 6860 | 7505 | 8255 | 8810 | 9270 |
| 25 | 6020 | 6590 | 7245 | 7735 | 8135 |
| 40 | 5180 | 5670 | 6235 | 6655 | 7005 |
| 50 | 4610 | 5045 | 5550 | 5925 | 6230 |
| 65 | 3810 | 4170 | 4585 | 4895 | 5150 |
| 70 | 3465 | 3795 | 4170 | 4455 | 4685 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.