


AGRIMAX PROHARVEST

TIRE SIZE	VF 900/60 R 32
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	MOISSONNEUSE
VERSION	STEEL BELTED
TIRE TYPE	TL
LI/SS	193 D



DIMENSIONS IS STANDARD

SW (MM)	881	RIM REC	DW 30 B
OD (MM)	1900	ECE	E11-106R-0010580
SLR (MM)	837	SRI	900
RC (MM)	5712		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
70	4085	4710	5340	6070	6700	7435	8270	8375	9735	10465
FROM 65 TO 40	4485	5175	5865	6670	7360	8165	9085	9200	10695	11500
30	4575	5280	5985	6805	7510	8330	9270	9385	10910	11730
20	4665	5385	6100	6940	7655	8495	9450	9570	11125	11960
10	4935	5695	6455	7340	8100	8985	9995	10120	11765	12650
UPTO 30 CYC	5095	5875	6660	7575	8360	9270	10315	10445	12145	13055
UPTO 15 CYC	6080	7015	7950	9040	9975	11070	12315	12470	14495	15585
UPTO 10 CYC	6665	7690	8715	9910	10935	12130	13495	13665	15885	17080
10HT	4575	5280	5985	6805	7510	8330	9270	9385	10910	11730

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.