

FLOTATION 648

TIRE SIZE	600/55 - 22.5
UM	IS STANDARD
CONSTRUCTION	⊗ BIAS
MACHINERY	PRESSA PER BALLE DI FIENO / MIETITREBBIA / SPARGITORE / MIETITREBBIA / ATTREZZI AGRICOLI
VERSIONE	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	151 A8/ 148 B
LI/SS FREE ROLLING	164 A8/160 B



DIMENSIONI IS STANDARD

SW (MM)	600	RIM REC	AG 20.00
OD (MM)	1230	ECE	E11-106R-004553
SLR (MM)	540	PR	12
RC (MM)	3716		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.50	1.70	2.00
10 FR	5915	6365	7000
20 FR	5325	5725	6300
30 FR	4730	5090	5600
40 FR	4225	4545	5000
50 FR	3805	4090	4500
10 DW	4080	4390	4830
20 DW	3675	3950	4345
30 DW	3265	3510	3865
40 DW	2915	3135	3450
50 DW	2625	2820	3150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.