


PL 801

| | |
|---------------------|--|
| TIRE SIZE | 8.25 - 15 |
| UM | IS STANDARD |
| CONSTRUCTION |  BIAS |
| MACHINERY | ADAINEUR ROTATIF / MOISSONNEUSE / CHARIOT ÉLÉVATEUR / MOISSONNEUSE / OUTILLAGE AGRICOLE / CHARIOT ÉLÉVATEUR |
| VERSION | STANDARD |
| TIRE TYPE | TT |



DIMENSIONS IS STANDARD

| | | | |
|----------------|----------|------------|-----------------|
| SW (MM) | 236 | ECE | E11-106R-003402 |
| OD (MM) | 854 | PR | 14 |
| RIM REC | 6.5 | | |
| RIM ALT | 6.0; 7.0 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 8.00 |
|---------------------------|-------------|
| 25 LOAD WHEEL | 4225 |
| 25 STEER WHEEL | 3250 |
| 10 OTHER VEHICLES | 4225 |
| 25 OTHER VEHICLES | 3250 |
| STATIC SIDE LOADER | 4910 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.