


# POWERTRAILER SR 331



<b>TIRE SIZE</b>	560/60 R 22.5
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRAILER / IMPLEMENTS / TANKER
<b>VERSION</b>	IMPLEMENT
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	169 D

## DIMENSIONS US STANDARD

<b>USA CODE</b>	94075997	<b>RIM REC</b>	AG 16.00
<b>OD (IN)</b>	49.0	<b>RIM ALT</b>	17.00; AG18.00
<b>SLR (IN)</b>	22.2	<b>ECE</b>	E11-106R-0010147
<b>RC (IN)</b>	148.6		

## LOAD CAPACITY (LBS/TIRE)

MPH/PSI	46	52	58	65	73	80	87
5	14960	16340	17960	19100	20250	21640	23020
15	13130	14340	15760	16770	17780	18990	20210
25	11300	12350	13570	14430	15300	16350	17390
30	10050	10990	12070	12840	13610	14540	15480
40	8310	9080	9970	10610	11250	12020	12800
43	7560	8260	9070	9660	10240	10930	11640

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.