

FLOTATION 648

TIRE SIZE	850/50 - 30.5
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	PRESSA PER BALLE DI FIENO / MIETITREBBIA / SPARGITORE / MIETITREBBIA / ATTREZZI AGRICOLI
VERSIONE	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	168 A8/164 B
LI/SS FREE ROLLING	180 A8/176 B



DIMENSIONI US STANDARD

CODICE USA	94006571	RC (IN)	194.3
SW (IN)	33.5	RIM REC	AG 28.00
OD (IN)	65.0	ECE	E11-106R-004564
SLR (IN)	28.0	PR	12

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	16	19	22
5 FR	20600	22720	24690
10 FR	18540	20450	22220
20 FR	16480	18180	19750
25 FR	14720	16230	17640
30 FR	13250	14600	15650
5 DW	14420	15890	17280
10 DW	12970	14310	15550
20 DW	11530	12720	13820
25 DW	10300	11350	12350
30 DW	9270	10220	11020

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.