

AGRIMAX TURF RT 333

480/70 R 34**UM** US STANDARD**CONSTRUCTION**  RADIAL**MACHINERY** ÜZÜM HASAT MAKINESİ / MEYVE
HASADI MAKINESİ / KÜÇÜK TRAKTÖR /
TRAKTÖR / BIÇERDÖVER**VERSION** STANDARD**TIRE TYPE** TL

149 A8 ; 149 B



UNDEFINED US STANDARD

USA CODE	94075232	RC (IN)	188.4
SW (IN)	19.3	RIM REC	W 15 L
OD (IN)	62.2	RIM ALT	W 14 L ; W 16 L
SLR (IN)	28.5	ECE	E11-106R-009042

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
30	3380	3870	4450	5020	5590	6170	6740	7170
25	3380	3870	4450	5020	5590	6170	6740	7170
20	3620	4150	4770	5380	5990	6610	7220	7680
5 LT	4520	5200	5970	6730	7500	8270	9030	9610
5 HT	3620	4150	4770	5380	5990	6610	7220	7680

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.