


# AGRIMAX PROCROP

<b>TIRE SIZE</b>	<b>VF 270/95 R 36</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	FELDSPRITZE
<b>VERSION</b>	STEEL BELTED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	150 D



## ABMESSUNGEN IS STANDARD

<b>SW (MM)</b>	280	<b>RIM REC</b>	W9
<b>OD (MM)</b>	1441	<b>ECE</b>	E11-106R-0010172
<b>SLR (MM)</b>	665	<b>SRI</b>	700
<b>RC (MM)</b>	4393		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1435	1620	1800	1955	2170	2290	2505	2715	2900	3050
FROM 65 TO 40	1575	1780	1980	2145	2380	2515	2750	2985	3185	3350
30	1610	1815	2020	2190	2430	2565	2805	3045	3250	3420
20	1640	1850	2060	2235	2475	2615	2860	3105	3315	3485
10	1735	1955	2175	2360	2620	2765	3025	3280	3505	3685

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.