

MULTIMAX MP 513

TIRE SIZE	425/55 R 17 MPT
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	УНИВЕРСАЛЬНЫЙ АВТОМОБИЛЬ / ТЕХНИКА ДЛЯ ВНЕСЕНИЯ УДОБРЕНИЙ / УНИВЕРСАЛЬНЫЙ АВТОМОБИЛЬ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	142 A8/B



РАЗМЕРЫ US STANDARD

USA CODE	94065110	RC (IN)	106.5
SW (IN)	16.6	RIM REC	13
OD (IN)	35.4	RIM ALT	13.00
SLR (IN)	15.7	ECE	E11-106R-006433

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	23	29	35	41	46	51	58
30	2280	2810	3340	3800	4330	4850	5380	5840
25	2280	2810	3340	3800	4330	4850	5380	5840
20	2450	3010	3570	4080	4640	5200	5580	6260
15	2540	3120	3700	4220	4810	5390	5790	6490

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.