


# AGRIMAXFACTOR

<b>TIRE SIZE</b>	<b>380/70 R 20</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRAKTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	132 D ; 135 A8



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94521104	<b>RC (IN)</b>	126.88
<b>SW (IN)</b>	14.88	<b>RIM REC</b>	W 12
<b>OD (IN)</b>	42.32	<b>RIM ALT</b>	W 11; W 13
<b>SLR (IN)</b>	19.05	<b>ECE</b>	E11-106R-0011740

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
40	1810	2120	2420	2730	3040	3310	3920	4410
30	1910	2230	2550	2880	3200	3470	4120	4630
25	1970	2310	2650	2990	3320	3600	4290	4810
20	2080	2440	2790	3150	3510	3800	4520	5070
5 LT	2420	2840	3250	3670	4080	4430	5270	5910
5 HT	2080	2440	2790	3150	3510	3800	4520	5070

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.