


# AGRIMAX V-FLECTO



<b>TIRE SIZE</b>	<b>VF 650/75 R 38</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTEUR DE FORTE PUISSANCE / TRACTEUR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	175 D

## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	675	<b>RIM REC</b>	DW 23 B
<b>OD (MM)</b>	1941	<b>RIM ALT</b>	DW 21 B
<b>SLR (MM)</b>	833	<b>ECE</b>	E11-106R-0010663
<b>RC (MM)</b>	5796	<b>SRI</b>	925

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
70	3450	4015	4580	5145	5710	6275
FROM 65 TO 40	3795	4415	5035	5655	6275	6900
30	3865	4500	5135	5765	6400	7035
20	3945	4590	5235	5880	6525	7175
10	4170	4855	5540	6220	6905	7590
*UPTO 10 CYC WITH FRONT LOADER	5310	6180	7050	7920	8790	9660
10HT	3865	4500	5135	5765	6400	7035

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.