


AGRIMAX RT 765

TIRE SIZE	380/70 R 20
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	PULVERIZATOR / TRACTOR / MAȘINĂ DE RECOLTAT PODGORII / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	132 A8/B



DIMENSIUNI US STANDARD

USA CODE	94021987	RC (IN)	126.5
SW (IN)	15.0	RIM REC	W 12
OD (IN)	42.6	RIM ALT	W 11; W 13
SLR (IN)	19.0	ECE	E4-106R-00648

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
30	2070	2380	2730	3090	3440	3790	4100	4400
25	2070	2380	2730	3090	3440	3790	4100	4400
20	2230	2560	2930	3310	3680	4070	4400	4720
5 LT	2780	3200	3670	4140	4620	5080	5500	5910
5 HT	2230	2560	2930	3310	3680	4070	4400	4720

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.