

# AGRIMAX RT 945

<b>TIRE SIZE</b>	<b>320/90 R 54</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ОПРЫСКИВАТЕЛЬ / ТРАКТОР-ТЯГАЧ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	156 A8/B



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94037094	<b>RC (IN)</b>	237.0
<b>SW (IN)</b>	12.6	<b>RIM REC</b>	W 10
<b>OD (IN)</b>	76.7	<b>RIM ALT</b>	W 9; W 11
<b>SLR (IN)</b>	36.6	<b>ECE</b>	E11-106R-003474

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	17	23	29	35	41	46	52	58	64	70
30	3310	4270	5160	5720	6040	6600	7160	7650	8050	8820	-
25	3310	4270	5160	5720	6040	6600	7160	7650	8050	8820	-
20	3540	4570	5520	6130	6470	7080	7670	8190	8620	9440	-
5	-	4100	5160	6350	7540	8730	8990	10050	11110	12170	13230

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.