

# FLOTATION 648

|                           |  |
|---------------------------|--|
| <b>TIRE SIZE</b>          | <b>500/60 - 22.5</b>   |
| <b>UM</b>                 | US STANDARD  |
| <b>CONSTRUCTION</b>       | ⊠ BIAS   |
| <b>MACHINERY</b>          | PRESSA PER BALLE DI FIENO /<br>MIETITREBBIA / SPARGITORE /<br>MIETITREBBIA / ATTREZZI AGRICOLI |
| <b>VERSIONE</b>           | STANDARD   |
| <b>TIRE TYPE</b>          | TL   |
| <b>LI/SS DRIVE WHEEL</b>  | 151 A8/148 B   |
| <b>LI/SS FREE ROLLING</b> | 163 A8/159 B   |



## DIMENSIONI US STANDARD

|                   |          |                |                |
|-------------------|----------|----------------|----------------|
| <b>CODICE USA</b> | 94006359 | <b>RC (IN)</b> | 137.4          |
| <b>SW (IN)</b>    | 19.7     | <b>RIM REC</b> | AG 16.00       |
| <b>OD (IN)</b>    | 46.1     | <b>RIM ALT</b> | 15.00; 17.00   |
| <b>SLR (IN)</b>   | 20.1     | <b>ECE</b>     | E4-106R-002308 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI    | 41    | 44    | 46    |
|--------------|-------|-------|-------|
| <b>5 FR</b>  | 13920 | 14490 | 15050 |
| <b>10 FR</b> | 12530 | 13040 | 13550 |
| <b>20 FR</b> | 11130 | 11600 | 12040 |
| <b>25 FR</b> | 9940  | 10350 | 10750 |
| <b>30 FR</b> | 8950  | 9310  | 9640  |
| <b>5 DW</b>  | 9840  | 10250 | 10650 |
| <b>10 DW</b> | 8860  | 9230  | 9580  |
| <b>20 DW</b> | 7880  | 8200  | 8520  |
| <b>25 DW</b> | 7030  | 7320  | 7610  |
| <b>30 DW</b> | 6330  | 6590  | 6940  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.