

# AS 504

<b>TIRE SIZE</b>	<b>10.0/75 - 15.3</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	SOLLEVATORE TELESOPICO / RIMORCHIO DA CAMPO / ATTREZZI AGRICOLI / SOLLEVATORE TELESOPICO
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	118 A8
<b>LI/SS FREE ROLLING</b>	130 A8



## DIMENSIONI IS STANDARD

<b>SW (MM)</b>	264	<b>RIM REC</b>	9.00
<b>OD (MM)</b>	785	<b>ECE</b>	E4-106R-001545
<b>SLR (MM)</b>	360	<b>PR</b>	14
<b>RC (MM)</b>	2404	<b>SRI</b>	360

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>5.50</b>
<b>10 FR</b>	2660
<b>25 FR</b>	2260
<b>30 FR</b>	2130
<b>40 FR</b>	1900
<b>10 DW</b>	1850
<b>25 DW</b>	1570
<b>30 DW</b>	1480
<b>40 DW</b>	1320

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.