

AGRIMAX V- FLECTO

VF 280/70 R 18

| | |
|--------------|--|
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | YÜKSEK GÜÇTE TRAKTÖR / TRAKTÖR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| | 116 D |



UNDEFINED IS STANDARD

| | | | |
|----------|------|---------|------------------|
| SW (MM) | 274 | RIM REC | W 9 |
| OD (MM) | 849 | RIM ALT | 9 |
| SLR (MM) | 375 | ECE | E11-106R-0010341 |
| RC (MM) | 2515 | SRI | 400 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 |
|--------------------------------|-----|------|------|------|------|------|
| 70 | 620 | 725 | 825 | 930 | 1030 | 1135 |
| FROM 65 TO 40 | 685 | 800 | 910 | 1025 | 1135 | 1250 |
| 30 | 700 | 815 | 930 | 1045 | 1160 | 1275 |
| 20 | 715 | 830 | 945 | 1065 | 1180 | 1300 |
| 10 | 755 | 880 | 1000 | 1125 | 1250 | 1375 |
| *UPTO 10 CYC WITH FRONT LOADER | 960 | 1120 | 1275 | 1435 | 1590 | 1750 |
| 10HT | 700 | 815 | 930 | 1045 | 1160 | 1275 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.