


# RIDEMAX FL 693 M



|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>650/65 R 30.5</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | CISTERNĂ / REMORCĂ / MAȘINI DE IMPLEMENTARE  |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 176 D  |

## DIMENSIUNI US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94075324 | <b>RC (IN)</b> | 194.4           |
| <b>SW (IN)</b>  | 25.4     | <b>RIM REC</b> | AG 20.00        |
| <b>OD (IN)</b>  | 63.9     | <b>ECE</b>     | E11-106R-009076 |
| <b>SLR (IN)</b> | 28.9     |                |                 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12   | 15    | 17    | 23    | 29    | 35    | 41    | 46    | 52    | 58    |
|-----------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45        | 4560 | 5280  | 6000  | 7270  | 8410  | 9700  | 10980 | 11840 | 13120 | 14250 |
| 40        | 5020 | 5800  | 6580  | 7990  | 9240  | 10650 | 12060 | 13000 | 14410 | 15650 |
| 30        | 6070 | 7020  | 7960  | 9670  | 11190 | 12890 | 14590 | 15730 | 17440 | 18950 |
| 25        | 6820 | 7890  | 8950  | 10870 | 12570 | 14480 | 16400 | 17680 | 19600 | 21300 |
| 15        | 7930 | 9160  | 10390 | 12620 | 14590 | 16820 | 19050 | 20530 | 22760 | 24730 |
| 5         | 9020 | 10430 | 11840 | 14370 | 16630 | 19170 | 21700 | 23390 | 25920 | 28170 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.