

EARTHMAX SR 47 TP



EARTHMAX SR 47 TP



EARTHMAX SR 47 TP (E-4) is an All-Steel radial tire specially engineered for rigid haul trucks operating in conditions requiring maximum traction and puncture resistance. The E-4 tread depth ensure long wear even on long hauls, thus reducing downtime and increasing productivity. EARTHMAX SR 47 TP is perfect for any task demanding both traction and stability particularly on muddy or slippery terrain. Available in standard and cut-resistant compounds.



	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH	O.W. (mm)	OD (mm)	SLR (mm)	RC (mm)	THREAD DEPTH	VERSION
						REC RIM	ALT RIM							
														
Ø35"	24.00 R 35	TL	E4	**	209 B	17.00/3.5	--	390	670	2185	985	6625	73	STD
	24.00 R 35	TL	E4	**	209 B	17.00/3.5	--	333	670	2185	985	6625	73	CR
	24.00 R 35	TL	E4	***	212 B	17.00/3.5	-	390	670	2185	985	6625	73	STD
	24.00 R 35	TL	E4	***	212 B	17.00/3.5	-	333	670	2185	985	6625	73	CR

STD: STANDARD, CR: CUT RESISTANT COMPOUND, STD: STANDARD COMPOUND

TECHNOLOGIES		PERFORMANCES	
			
			
B	212 kg		
			
			

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index