

# FL 695

<b>TIRE SIZE</b>	<b>600/60 R 30.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ПРИЦЕП / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП
<b>VERSION</b>	STEEL BELTED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	179 D



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	611	<b>RIM REC</b>	AG20.00
<b>OD (MM)</b>	1495	<b>ECE</b>	E11-106R-008503
<b>SLR (MM)</b>	693	<b>SRI</b>	725
<b>RC (MM)</b>	4586		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.5	5.0	5.5	6.0
65	--	--	--	3490	4030	4575	5040	5505	6045	6435	6820	7285	7750
50	--	--	--	4225	4880	5535	6100	6660	7320	7790	8255	8820	9380
40	--	3480	4325	4745	5485	6220	6855	7485	8225	8750	9280	9910	10540
30	2930	3865	4800	5270	6090	6910	7610	8315	9130	9720	10305	11005	11705
25	3065	4045	5025	5515	6370	7225	7960	8695	9555	10165	10780	11515	12245
20	3200	4225	5245	5760	6655	7550	8315	9085	9980	10620	11260	12025	12790
10	3490	4605	5720	6280	7255	8235	9070	9905	10885	11580	12280	13115	13950

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.