


# AGRIMAX TERIS

<b>TIRE SIZE</b>	<b>750/65 R 26 CHO</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	CEIFEIRA / COLHEDORA DE ALGODÃO
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	166 A8/B



## DIMENSÕES IS STANDARD

<b>SW (MM)</b>	764	<b>RIM REC</b>	DW 25 B
<b>OD (MM)</b>	1636	<b>RIM ALT</b>	DW 23 B
<b>SLR (MM)</b>	713	<b>ECE</b>	E4-106R-000810
<b>RC (MM)</b>	4908	<b>SRI</b>	750

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.4	1.6	2.0	2.4
50	2915	3340	4085	4400	4930	5300
40	2915	3340	4085	4400	4930	5300
30	3125	3580	4370	4715	5280	5675
15 CYC	4810	5510	6735	7260	8135	8745
10 CYC	5250	6015	7350	7920	8875	9540

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.