

AGRIMAX SPARGO SB

TIRE SIZE	VF 380/90 R 50
UM	IS STANDARD
CONSTRUCTION	
MACHINERY	TRACTOR / SPRAYER
VERSION	STEEL BELTED
TIRE TYPE	TL
LI/SS	175 D



DIMENSIONS IS STANDARD

SW (MM)	400	RIM REC	W13
OD (MM)	1954	RIM ALT	W12;DW13
SLR (MM)	903	ECE	E11-106R-0010177
RC (MM)	5986	SRI	925

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.0	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2	3.4	3.6	3.8	4.0	4.2	4.4
70	2705	3015	3395	3710	3895	4085	4210	4335	4555	4775	4965	5150	5310	5465	5625	5780	6030	6280
FROM 65 TO 40	2970	3315	3730	4075	4280	4485	4625	4765	5005	5245	5455	5660	5835	6005	6180	6350	6625	6900
30	3030	3380	3805	4155	4365	4580	4720	4860	5105	5355	5565	5775	5950	6125	6305	6480	6760	7040
20	3090	3450	3880	4240	4455	4670	4815	4955	5210	5460	5675	5890	6070	6250	6430	6610	6895	7180
10	3265	3645	4100	4480	4710	4935	5090	5240	5505	5770	6000	6225	6415	6605	6795	6985	7290	7590

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.