

AGRIMAX TURF RT 333

TIRE SIZE	280/70 R 18
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	MAȘINĂ DE RECOLTAT PODGORII / RECOLTAREA LIVEZILOR / TRACTOR MIC / TRACTOR / MAȘINĂ DE RECOLTARE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	114 A8 ; 114 B



DIMENSIUNI IS STANDARD

SW (MM)	289	RIM REC	W 9
OD (MM)	840	RIM ALT	W 8; W 10
SLR (MM)	390	ECE	E11-106R-006473
RC (MM)	2550	SRI	400

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	555	640	735	830	925	1015	1110	1180
40	555	640	735	830	925	1015	1110	1180
30	595	685	785	890	990	1090	1190	1265
10 LT	745	860	985	1110	1240	1365	1490	1585
10 HT	595	695	785	890	990	1090	1190	1265

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.