


# AGRIMAX RT 765

|                     |  |
|---------------------|--|
| <b>TYRE SIZE</b>    | <b>600/70 R 30</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | TRACTOR / IMPLEMENTS   |
| <b>VERSION</b>      | SPECIAL  |
| <b>TYRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 152 D  |



## DIMENSIONS IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 611  | <b>RIM REC</b> | DW 20 B         |
| <b>OD (MM)</b>  | 1602 | <b>RIM ALT</b> | DW 18 L; W 18 L |
| <b>SLR (MM)</b> | 711  | <b>ECE</b>     | E11-106R-005523 |
| <b>RC (MM)</b>  | 4774 | <b>SRI</b>     | 750             |

## LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  |
|------------|------|------|------|------|------|------|
| 65         | 1955 | 2275 | 2595 | 2915 | 3235 | 3550 |
| 50         | 2055 | 2390 | 2725 | 3060 | 3395 | 3730 |
| 40         | 2140 | 2490 | 2840 | 3190 | 3540 | 3890 |
| 30         | 2250 | 2615 | 2985 | 3350 | 3720 | 4085 |
| 10 LT      | 2620 | 3050 | 3475 | 3905 | 4335 | 4760 |
| 10 HT      | 2250 | 2615 | 2985 | 3350 | 3720 | 4085 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.