

# EARTHMAX SR 46

|           |                         |
|-----------|-------------------------|
| TIRE SIZE | 33.00 R 51              |
| UM        | IS STANDARD             |
| MACHINERY | DUMPER RIGIDO           |
| VERSIONE  | HEAT RESISTANT COMPOUND |
| TIRE TYPE | TL                      |
| LI/SS     | 235 B                   |

## DIMENSIONI IS STANDARD

|          |           |             |    |
|----------|-----------|-------------|----|
| OD (MM)  | 3050      | TRA CODE    | E4 |
| SLR (MM) | 1401      | STAR RATING | ★★ |
| RC (MM)  | 9377      |             |    |
| RIM REC  | 24.00/5.0 |             |    |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 5.00  | 5.25  | 5.50  | 5.75  | 6.00  | 6.25  | 6.50  | 6.75  | 7.00  |
|------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 50         | 30000 | 30750 | 32500 | 33500 | 34500 | 35500 | 36500 | 37500 | 38750 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

