

# FLOTATION 648

<b>TIRE SIZE</b>	500/50 - 22.5
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	BIAS
<b>MACHINERY</b>	BALPRESS / SKÖRDEMASKIN / SPRIDARE / SKÖRDEMASKIN / ARBETSFORDON
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	140 A8/136 B
<b>LI/SS FREE ROLLING</b>	152 A8/148 B



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94027798	<b>RC (IN)</b>	126.0
<b>SW (IN)</b>	19.7	<b>RIM REC</b>	AG 16.00
<b>OD (IN)</b>	42.1	<b>PR</b>	12
<b>SLR (IN)</b>	18.7		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	22	29	32
5 FR	8750	10350	10960
10 FR	7870	9310	9870
20 FR	7000	8290	8760
25 FR	6250	7400	7830
30 FR	5620	6660	6940
5 DW	6170	7300	7720
10 DW	5560	6570	6940
20 DW	4940	5840	6170
25 DW	4410	5210	5510
30 DW	3970	4700	4940

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.