


# AGRIMAX FORCE

<b>TIRE SIZE</b>	<b>IF 710/70 R 42</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SKÖRDEMASKIN / MOTORSTARK TRAKTOR / TRAKTOR
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	179 D



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94060078	<b>RC (IN)</b>	242.8
<b>SW (IN)</b>	28.2	<b>RIM REC</b>	DW 25 B
<b>OD (IN)</b>	81.1	<b>RIM ALT</b>	DW 23 B
<b>SLR (IN)</b>	36.2	<b>ECE</b>	E4-106R-001830

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	7300	8390	9630	10880	12120	13370	14600	15540
<b>FROM 40 TO 25</b>	8020	9230	10590	11960	13330	14690	16060	17100
20	8340	9590	11010	12430	13860	15280	16700	17770
12	8660	9950	11430	12910	14380	15860	17340	18450
5	10180	11710	13450	15180	16920	18650	20390	21690
<b>UPTO 20 CYC</b>	10430	11990	13770	15540	17320	19090	20880	22210
<b>UPTO 10 CYC</b>	12430	14300	16410	18530	20650	22770	24890	26480
<b>UPTO 5 CYC</b>	13630	15670	18000	20330	22650	24980	27290	29040
5 HT	8340	9590	11010	12430	13860	15280	16700	17770

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.