


# AGRIMAX TERIS

<b>TIRE SIZE</b>	<b>750/65 R 26</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MIETITREBBIA / RACCOGLITRICE DI COTONE
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	171 A8/B



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94039111	<b>RC (IN)</b>	193.2
<b>SW (IN)</b>	30.1	<b>RIM REC</b>	DW 25 B
<b>OD (IN)</b>	64.4	<b>RIM ALT</b>	DW 23 B
<b>SLR (IN)</b>	28.1	<b>ECE</b>	E4-106R-001496

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	20	23	29	35	41	46
30	6430	7360	9010	9700	10870	11680	12610	13560
25	6430	7360	9010	9700	10870	11680	12610	13560
20	6890	7890	9630	10390	11640	12510	13500	14520
10 CYC	10600	12150	14850	16000	17930	19280	20810	22380
5 CYC	11570	13260	16200	17460	19560	21030	22710	24400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.