

# ROCK GRIP IND4 (ECH)

|                     |                       |
|---------------------|-----------------------|
| <b>TIRE SIZE</b>    | <b>14.00 - 24</b>     |
| <b>UM</b>           | US STANDARD           |
| <b>CONSTRUCTION</b> | ⊠ BIAS                |
| <b>MACHINERY</b>    | TOMCONTAINERHANTERARE |
| <b>VERSION</b>      | PORT INDUSTRIAL       |
| <b>TIRE TYPE</b>    | TL                    |



## DIMENSIONER US STANDARD

|                 |          |                 |          |
|-----------------|----------|-----------------|----------|
| <b>USA CODE</b> | 94059201 | <b>RIM REC</b>  | 10.00 WA |
| <b>OD (IN)</b>  | 55.5     | <b>RIM ALT</b>  | 10.00 VA |
| <b>SLR (IN)</b> | 25.5     | <b>PR</b>       | 32       |
| <b>RC (IN)</b>  | 164.3    | <b>TRA CODE</b> | IND4     |

## LOAD CAPACITY (LBS/TIRE)

|                  |            |
|------------------|------------|
| <b>MPH / PSI</b> | <b>145</b> |
| 5                | 31250      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.