


AGRIMAX TURF RT 333

TIRE SIZE	260/70 R 16
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	SKÖRDEMASKIN FÖR VINGÅRD / SKÖRDEMASKIN FÖR FRUKTODLING / LITEN TRAKTOR / TRAKTOR / SKÖRDEMASKIN
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	109 A8 ; 109 B



DIMENSIONER IS STANDARD

SW (MM)	258	RIM REC	W 8
OD (MM)	770	RIM ALT	W 8 L; W 9
SLR (MM)	348	ECE	E11-106R-007158
RC (MM)	2287	SRI	370

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	485	560	640	725	805	890	970	1030
40	485	560	640	725	805	890	970	1030
30	520	600	690	775	865	955	1040	1105
10 LT	655	750	860	970	1085	1195	1305	1385
10 HT	520	600	690	775	865	955	1040	1105

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.