


# RIDEMAX FL 693 M



|                     |                                                                                          |
|---------------------|------------------------------------------------------------------------------------------|
| <b>TYRE SIZE</b>    | <b>425/55 R 17</b>                                                                       |
| <b>UM</b>           | US STANDARD                                                                              |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | TRAILER / IMPLEMENTS                                                                     |
| <b>VERSION</b>      | STANDARD                                                                                 |
| <b>TL/TT</b>        | TL                                                                                       |
| <b>LI/SS</b>        | 129 D ; 140 A8                                                                           |

## DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94059324 | <b>RC (IN)</b> | 106.5           |
| <b>SW (IN)</b>  | 16.5     | <b>RIM REC</b> | 13.00           |
| <b>OD (IN)</b>  | 35.2     | <b>ECE</b>     | E11-106R-005104 |
| <b>SLR (IN)</b> | 15.6     |                |                 |

## LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 12   | 17   | 23   | 29   | 35   | 41   | 46   | 52   | 58   |
|-----------|------|------|------|------|------|------|------|------|------|
| 40        | 1310 | 1680 | 2080 | 2370 | 2730 | 3110 | 3390 | 3710 | 4080 |
| 30        | 1590 | 2030 | 2520 | 2870 | 3320 | 3760 | 4100 | 4500 | 4940 |
| 25        | 1760 | 2260 | 2810 | 3200 | 3690 | 4190 | 4570 | 5020 | 5510 |
| 20        | 1970 | 2540 | 3150 | 3580 | 4130 | 4680 | 5110 | 5610 | 6160 |
| 15        | 2070 | 2650 | 3300 | 3750 | 4320 | 4910 | 5360 | 5870 | 6450 |
| 5         | 2360 | 3020 | 3750 | 4270 | 4930 | 5590 | 6100 | 6690 | 7340 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.