


FL 639

TIRE SIZE	600/50 R 22.5
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ÉPANDEUR / OUTILLAGE AGRICOLE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	159 D ; 170 A8



DIMENSIONS IS STANDARD

SW (MM)	611	RIM REC	AG 20.00
OD (MM)	1172	ECE	E4-106R-000802
SLR (MM)	530	SRI	550
RC (MM)	3540		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1280	1480	1675	2020	2355	2680	3020	3330	3670	3985
65	1400	1620	1840	2220	2585	2950	3310	3660	4025	4375
50	1695	1960	2225	2700	3125	3575	4000	4420	4875	5295
40	1920	2220	2520	3040	3540	4050	4555	5020	5520	6000
25	2215	2560	2905	3510	4080	4675	5210	5800	6365	6915
10	2520	2915	3310	4000	4650	5325	5940	6600	7245	7875

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.