


AGRIMAX FORCE

TIRE SIZE	IF 620/75 R 30
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	КОМБАЙН / ТРАКТОР ВЫСОКОЙ МОЩНОСТИ / ТРАКТОР-ТЯГАЧ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	169 D



РАЗМЕРЫ US STANDARD

USA CODE	94064717	RC (IN)	200.8
SW (IN)	25.6	RIM REC	DW 23 B
OD (IN)	67.0	RIM ALT	DW 21 B
SLR (IN)	29.9	ECE	E11-106R-006496

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	5460	6270	7210	8130	9060	10000	10920	11630
FROM 40 TO 25	6010	6900	7930	8950	9960	10990	12010	11355
20	6240	7180	8230	9300	10360	11420	12490	13290
12	6480	7450	8550	9660	10760	11860	12970	13800
5	7630	8760	10060	11360	12650	13950	15260	16240
UPTO 20 CYC	7800	8960	10300	11630	12950	14290	15620	16620
UPTO 10 CYC	9300	10690	12280	13870	15440	17030	18620	19820
UPTO 5 CYC	10210	11730	13470	15210	16930	18670	20420	21740
5 HT	6240	7180	8230	9300	10360	11420	12490	13290

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.